



用途

保温截止阀，是主要用于石油、化工、冶金、制药等各类系统中，以输送常温下会凝固的高粘度介质，是BJ45W直流夹套保温截止阀的保温夹套焊接于阀门的两法兰之间，阀门的侧面、底部设置有保温夹套的两个连接口。直流保温截止阀特别适用于化工、化肥行业的管路上，夹套内通入蒸汽能防止介质结晶。保温截止阀被广泛应用于石油、化工、冶金、制药等各类系统中。

Purpose

The utility model relates to a thermal insulation stop valve, which is mainly used in petroleum, chemical industry, metallurgy, pharmacy, etc. High viscosity media will be solidified at room temperature, is the BJ45W DC jacket insulation valve Between the temperature jacket valve two in welding flange, side and bottom valve is provided with an insulating jacket Two connecting ports. DC insulation valve is particularly suitable for chemical industry, fertilizer industry pipeline, Jacket into the steam can prevent the crystallization of media. Insulation stop valve is widely used in petroleum, chemical Engineering, metallurgy, pharmaceutical and other systems.

主要连接尺寸及重量 Main Connection Dimensions and Weight

DN	L	D	D1	D2	D6	b	Z-φd	G	H	D0	WT (kg)
BJ45H-16 BJ45Y-16P BJ45Y-16R BJ45Y-16R3											
15	130	95	65	45	-	16	4-Φ14	1/2"	170	120	-
20	150	105	75	55	-	16	4-Φ14	1/2"	190	140	-
25	160	115	85	65	-	16	4-Φ14	1/2"	205	160	-
32	180	135	100	78	-	18	4-Φ18	1/2"	270	180	-
40	200	145	110	85	-	18	4-Φ18	1/2"	310	200	-
50	230	160	125	100	-	18	4-Φ18	3/4"	358	240	-
65	290	180	145	120	-	18	4-Φ18	3/4"	373	280	-
80	310	195	160	135	-	20	8-Φ18	3/4"	435	320	-
100	350	215	180	155	-	20	8-Φ18	1	500	360	-
125	400	245	210	185	-	22	8-Φ18	1	614	400	-
150	480	280	240	210	-	24	8-Φ23	1	674	400	-
200	600	335	295	265	-	26	12-Φ23	1	818	450	-

主要连接尺寸及重量 Main Connection Dimensions and Weight											
DN	L	D	D1	D2	D6	b	Z-Φd	G	H	D0	WT (kg)
BJ45H-25 BJ45Y-25P BJ45Y-25R BJ45Y-25R3											
15	200	105	75	55	-	16	4-Φ14	1/2"	210	120	-
20	220	115	85	65	-	16	4-Φ14	1/2"	240	140	-
25	220	135	100	78	-	18	4-Φ18	1/2"	250	160	-
32	250	145	110	85	-	18	4-Φ18	1/2"	270	160	-
40	270	160	125	100	-	20	4-Φ18	1/2"	310	160	-
50	300	180	145	120	-	22	8-Φ18	3/4"	330	240	-
65	350	195	160	135	-	22	8-Φ18	3/4"	360	240	-
80	380	230	190	160	-	24	8-Φ23	3/4"	400	280	-
100	430	270	220	188	-	28	8-Φ25	1	480	320	-
125	490	300	250	218	-	30	8-Φ25	1	550	360	-
150	570	330	280	248	-	32	12-Φ25	1	620	300	-
200	690	395	340	302	-	36	12-Φ30	1	750	400	-
BJ45H-40 BJ45Y-40P BJ45Y-40R BJ45Y-40R3											
15	20	105	75	55	51	16	4-Φ14	1/2"	210	120	-
20	220	115	85	65	58	16	4-Φ14	1/2"	240	140	-
25	220	135	100	78	66	18	4-Φ18	1/2"	250	160	-
32	250	145	110	85	76	18	4-Φ18	1/2"	270	160	-
40	270	160	125	100	88	20	4-Φ18	1/2"	310	160	-
50	300	180	145	120	110	22	8-Φ18	3/4"	330	240	-
65	350	195	160	135	121	22	8-Φ18	3/4"	360	240	-
80	380	230	190	160	150	24	8-Φ23	3/4"	400	280	-
100	430	270	220	188	176	28	8-Φ25	1	480	320	-
125	190	300	250	218	204	30	8-Φ25	1	550	360	-
150	570	350	295	258	234	34	12-Φ30	1	620	360	-
200	690	415	355	315	287	40	12-Φ34	1	750	400	-